

inverTITAN

POWERFUL PERFORMANCE. EFFICIENT OPERATION.

Designed and engineered to meet the highest requirements for cooling and heating options, with full inverter compressor and top discharge fans for a streamlined efficient air flow. Powerful performance supported by the latest eco-friendly technology. Enjoy new possibilities for pool heating and cooling with the space saving and slick design of the InverTITAN. Limited space is no longer a concern. Full Stepless DC Compressor, marine grade aluminium alloy casing, Twisted Titanium Heat Exchanger and Madimack's Advanced Sound Suppression Technology for whisper quiet operation.

Trusted by
POOL PROFESSIONALS



Heat & Cool

With integrated heating and cooling into a single unit, enjoy your swimming pool any season of the year



Operation down to 14°F

Built to operate in the coldest weather and extend your pool season into the winter



Built-in Wi-Fi

Built-in Wi-Fi and a smart app provide convenience to control your pump on-the-go



Twin-rotary compressor

Significantly reduced operating noise



Electronic expansion valve

Optimized flow of refrigerant 20% higher COP



Twisted titanium heat exchanger

Increased area for heat exchange 40% higher efficiency



Smart & quick defrosting

InverTITAN is equipped with reverse cycle defrosting detecting frost accumulation during operation and automatically switch to defrosting mode



advanced
sound
suppression
technology



Globally Recognized. Industry Respected.



madimack

Powered by

INVERMAC
TECHNOLOGY

866-682-9276



TECHNICAL PARAMETERS

Model Name	inverTITAN 90,000	inverTITAN 112,000	inverTITAN 140,000
Model Number	ITVC090	ITVC112	ITVC140
SKU	INVTIT090	INVTIT112	INVTIT140
PERFORMANCE CONDITION: AIR 80°F / WATER 80°F / HUMIDITY 80%			
Heating capacity (BTU)	80,000	107,000	133,000
COP Range	5.9	5.7	5.2
PERFORMANCE CONDITION: AIR 80°F / WATER 80°F / HUMIDITY 63%			
Heating capacity (BTU)	77,000	100,000	119,000
COP Range	5.7	5.4	4.9
PERFORMANCE CONDITION: AIR 50°F / WATER 80°F / HUMIDITY 63%			
Heating capacity (BTU)	41,500	51,000	58,000
COP Range	4.4	4.4	4.2
TECHNICAL SPECIFICATIONS			
Cooling capacity (BTU)	42,000	56,000	69,000
Temperature set point range (°F/ °C)	64~104/ 18~40		
Operating air temperature (°F/ °C)	14 ~ 109/ -10~43		
Heat exchanger	Titanium in PVC		
Power supply	208 ~ 230V/1 Ph/60Hz		
Electrical Connection	Hardwired (3 × 10 AWG/ 3 × 6.0 mm ²)	Hardwired (3 × 8.0 AWG/ 3 × 10 mm ²)	Hardwired (3 × 6.0 AWG/ 3 × 16 mm ²)
Minimum Circuit Ampacity (MCA)	25	40	50
Max. Rating Overcurrent Protection (MOP)	25	60	80
Rated input power (kW) at air 80°F	0.57 ~ 4.40	0.7 ~ 5.38	0.89 ~ 6.84
Rated input current (A) at air 80°F	2.49 ~ 19.13	3.04 ~ 23.39	3.87 ~ 29.74
Sound level at 10ft dB(A)	34.3 ~ 46.5	35.2 ~ 48.3	38.8 ~ 51.1
Maximum input current (A)	21.5	32.5	40
Advised water flux/ flow ± 20% (GPM/ LPM)	33.0 ~41.7/ 125 ~ 158	35.1 ~ 48.3/ 133 ~ 167	35.1 ~ 67.1/ 133 ~ 254
Water Pressure Drop (kPA)	6	10	19
Water connection (inch/ mm)	2/ 50		
Refrigerant Gas	R410A		
Maximum Air Volume ((m ³ /h)	6500	7500	8300
Net dimension LxWxH	35.7" × 27.6" × 38.5"/ 906 × 701 × 977	35.7" × 27.6" × 38.5"/ 906 × 701 × 977	39.1" × 31.7" × 41.5"/ 992 × 806 × 1054
Net Weight (lb/ kg)	277.8/ 126	275.6/ 125	315.3/ 143
Gross Weight (lb/ kg)	313.1/ 142	317.5/ 144	407.9/ 185
Packaging dimension LxWxH (inch/ mm)	39.0" × 29.4" × 39.8"/ 990 × 746 × 1010	39.0" × 29.4" × 39.8"/ 990 × 746 × 1010	42.1" × 33.9" × 42.9"/ 1070 × 860 × 1090

*The data above is only for reference. For specific data, please

866-682-9276

madimack